## IN THE CLAIMS:

1. (Previously presented) A method of displaying a video signal, comprising the steps of:

retrieving the video signal;

generating a graphical display including a bar extending in a predetermined direction and divided into at least two program sections, the sections defined by markers, said markers capable of having been generated when a user changes the channel and whereby a program marker will only have been inserted when a user had selected a new channel and had remained on the new channel in excess of a predetermined period of time; wherein at least one of the markers is capable of indicating when a user changes a channel prior to conclusion of a program:

inserting the graphical display into the video signal; and outputting the video signal.

- (Currently amended) The method of claim 1, wherein the <u>predetermined period of</u> time is selected from periods of time consisting of 20, 30, 60 and 120 seconds, <del>program</del> sections defined by the markers may be less than 120 seconds.
- 3. (Previously presented) The method of claim 1, wherein the markers correspond to either a program change or a channel change.
- (Original) The method of claim 1, wherein the program sections are color coded to indicate genre of a program.
- (Original) The method of claim 1, wherein at least one of the program sections is color coded to indicate a program is copy-protected.
- (Original) The method of claim 1, wherein at least one of the program sections is color coded to indicate a program is to be saved.

- (Previously presented) The method of claim 1, wherein at least one of the program sections is color coded to indicate no signal available at time of recording.
- (Original) The method of claim 1, wherein the graphical display further includes a program pointer.
- (Original) The method of claim 1, wherein the graphical display further includes a start time graphic and an end time graphic.
- 10. (Original) The method of claim 1, wherein the graphical display further includes an in flow animation and an out flow animation.

11. (Currently amended) A personal video recording device, comprising:

a buffer for storing a video signal;
an audio and video coding unit for retrieving and decoding the video signal;
generating a graphical display including a bar extending in a predetermined
direction and dividing the bar into at least two program sections, the sections defined by
markers, said markers capable of having been generated when a user changes the channel
and whereby a program marker will only have been inserted when a user had selected a
new channel and had remained on the new channel in excess of a predetermined period of
time; wherein at least one of the markers is capable of indicating when a user changes a
channel prior to conclusion of a program;

inserting the graphical display into the video signal; and a switch for outputting the video signal.

- 12. (Currently amended) The device of claim 11, wherein the <u>predetermined period of time is selected from periods of time consisting of 20, 30, 60 and 120 seconds. program sections defined by the markers may be less than 120 seconds.</u>
- 13. (Previously presented) The device of claim 11, wherein the markers correspond to

either a program change or a channel change.

- 14. (Original) The device of claim 11, wherein the program sections are color coded to indicate genre.
- 15. (Original) The device of claim 11, wherein at least one of the program sections is color coded to indicate a program is copy-protected.
- 16. (Original) The device of claim 11, wherein at least one of the program sections is color coded to indicate a program is to be saved.
- 17. (Previously presented) The device of claim 11, wherein at least one of the program sections is color coded to indicate no signal available at time of recording.
- 18. (Original) The device of claim 11, wherein the graphical display further includes a program pointer.
- 19. (Original) The device of claim 11, wherein the graphical display further includes a start time graphic and an end time graphic.
- 20. (Original) The device of claim 11, wherein the graphical display further includes an in flow animation and an out flow animation.
- 21. (Currently amended) A graphical display for a personal recording device, comprising:
  - a bar extending in a predetermined direction;
- markers dividing the bar into at least two program sections, the sections defined by markers, <u>said markers capable of having been generated when a user changes the</u> <u>channel and whereby a program marker will only have been inserted when a user had</u> <u>selected a new channel and had remained on the new channel in excess of a</u>

<u>predetermined period of time;</u> wherein at least one of the markers is capable of indicating when a user changes a channel prior to conclusion of a program;, and

a program pointer.